



GOOD QUALITY BEARINGS LIMITED

TIMKEN MSM60BXHFATL Flange Block Bearings



MSM60BXHFATL Bearing 2D drawings and 3D CAD models

Bearing No. MSM60BXHFATL

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	21.64
EAN	0013992050472
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	MSM60BX
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Pilot Configuration	No Pilot
Inch - Metric	Metric
Long Description	4 Bolt Round Flange Block; 60MM Bore; 242MM Bolt Circle; 2 Piece Split; Clamp Collar Mount; Cast Iron; Cylindrical Roller Bearing; 72.3MM Length Thru Bore; 171.1MM Bolt Spacing; Relubricatable; Triple



GOOD QUALITY BEARINGS LIMITED

Other Features	Single Row Wide Inner Ring Medium Duty
Category	Flange Block Bearings
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Weight / LBS	47.67
Nominal Bolt Circle Diameter Round	9.5 Inch 242 Millimeter
d	2.362 Inch 60 Millimeter
D	2.846 Inch 72.3 Millimeter
Bolt Spacing	6.7 Inch 171.1 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Shaft Size	60 mm
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Expansion Type
Support Type	Round Flange
Series Type	Medium Series
Bolt Size	4 x M12
Bearing - Housing - Seal	MSM60BXHATL
Bearing - Housing - Seal UPC	013992043771
Bearing UPC	013992035028
Dimension T	11.3 in
Dimension R	9.5 in
Dimension P	0.6 in
Dimension H	2.9 in
Dimension N	7.563 in
Dimension V	0.1 in



GOOD QUALITY BEARINGS LIMITED

Dimension L	5.4 in
Cr - Dynamic Load Rating	37768 lbf
Cor - Static Load Rating	42714 lbf
Maximum Speed	3680 rpm
Note	This product line was formerly known as " Revolve "