



GOOD QUALITY BEARINGS LIMITED



MSM80BRHFATL Bearing 2D drawings and 3D CAD models

TIMKEN MSM80BRHFATL Flange Block Bearings

Bearing No. MSM80BRHFATL

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	40.84
EAN	0013992051325
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	MSM80BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Pilot Configuration	No Pilot
Inch - Metric	Metric
Long Description	4 Bolt Round Flange Block; 80MM Bore; 302MM Bolt Circle; 2 Piece Split; Clamp Collar Mount; Cast Iron; Cylindrical Roller Bearing; 89.7MM Length Thru Bore; 213.5MM Bolt Spacing; Relubricatable; Triple



GOOD QUALITY BEARINGS LIMITED

Other Features	Single Row Wide Inner Ring Medium Duty
Category	Flange Block Bearings
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Weight / LBS	89.96
Nominal Bolt Circle Diameter Round	11.9 Inch 302 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
d	3.15 Inch 80 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
D	3.531 Inch 89.7 Millimeter
Bolt Spacing	8.4 Inch 213.5 Millimeter
Shaft Size	80 mm
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Round Flange
Series Type	Medium Series
Bolt Size	4 x M16
Bearing - Housing - Seal	MSM80BRHATL
Bearing - Housing - Seal UPC	013992044723
Bearing UPC	013992035332
Dimension T	14.0 in
Dimension R	11.9 in
Dimension P	0.7 in
Dimension H	3.4 in
Dimension N	9.625 in
Dimension V	0.1 in



GOOD QUALITY BEARINGS LIMITED

Dimension L	6.4 in
Cr - Dynamic Load Rating	66768 lbf
Cor - Static Load Rating	79358 lbf
Ca - Axial Load Rating	4002 lbf
Maximum Speed	2520 rpm
Note	This product line was formerly known as “ Revolve ”