



# GOOD QUALITY BEARINGS LIMITED

## TIMKEN MSE200BRHFATL Flange Block Bearings



MSE200BRHFATL Bearing 2D drawings and 3D CAD models

Bearing No. MSE200BRHFATL

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	15.6
EAN	0013992046925
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	12 Millimeter
Relubricatable	Yes
Insert Part Number	MSE200BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Block; 2" Bore; 8.6" Bolt Circle; 2 Piece Split; Clamp Collar Mount; Cast Iron; Cylindrical Roller Bearing; 2.657" Length Thru Bore; 6.1" Bolt Spacing; Relubric



## GOOD QUALITY BEARINGS LIMITED

Other Features	Single Row   Wide Inner Ring   Medium Duty
Category	Flange Block Bearings
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Weight / LBS	34.36
D	2.657 Inch   67.5 Millimeter
d	2 Inch   50.8 Millimeter
Nominal Bolt Circle Diameter Round	8.6 Inch   218 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Bolt Spacing	6.1 Inch   154.9 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Shaft Size	2 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Round Flange
Series Type	Medium Series
Bolt Size	4 x M12
Bearing - Housing - Seal	MSE200BRHATL
Bearing - Housing - Seal UPC	013992059017
Bearing UPC	013992031792
Dimension T	10.2 in
Dimension R	8.6 in
Dimension P	0.6 in
Dimension H	2.6 in
Dimension N	6.571 in
Dimension V	0.1 in



## GOOD QUALITY BEARINGS LIMITED

Dimension L	4.8 in
Cr - Dynamic Load Rating	27202 lbf
Cor - Static Load Rating	28551 lbf
Ca - Axial Load Rating	1394 lbf
Maximum Speed	4350 rpm
Note	This product line was formerly known as " Revolve "