



GOOD QUALITY BEARINGS LIMITED

TIMKEN MSE308BRHFATL Flange Block Bearings



MSE308BRHFATL Bearing 2D drawings and 3D CAD models

Bearing No. MSE308BRHFATL

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	39.89
EAN	0013992048721
Product Group	B04144
Number of Mounting Holes	4
Mounting Method	Clamp Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Cylindrical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-Expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	MSE308BR
Seals	Triple Lip Labyrinth
Housing Configuration	2 Piece Split
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Block; 3-1/2" Bore; 11.9" Bolt Circle; 2 Piece Split; Clamp Collar Mount; Cast Iron; Cylindrical Roller Bearing; 3-17/32" Length Thru Bore; 8.4" Bolt Spacing; R



GOOD QUALITY BEARINGS LIMITED

Other Features	Single Row Wide Inner Ring Medium Duty
Category	Flange Block Bearings
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Weight / LBS	87.87
d	3.5 Inch 88.9 Millimeter
Bolt Spacing	8.4 Inch 213.5 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
D	3.531 Inch 89.7 Millimeter
Nominal Bolt Circle Diameter Round	11.9 Inch 302 Millimeter
Shaft Size	3.5 in
Seal Type	Aluminium Triple Labyrinth
Bearing Type	Split Cylindrical Retained Type
Support Type	Round Flange
Series Type	Medium Series
Bolt Size	4 x M16
Bearing - Housing - Seal	MSE308BRHATL
Bearing - Housing - Seal UPC	013992061218
Bearing UPC	013992032218
Dimension T	14.0 in
Dimension R	11.9 in
Dimension P	0.7 in
Dimension H	3.4 in
Dimension N	9.625 in
Dimension V	0.1 in



GOOD QUALITY BEARINGS LIMITED

Dimension L	6.4 in
Cr - Dynamic Load Rating	66768 lbf
Cor - Static Load Rating	79358 lbf
Ca - Axial Load Rating	4002 lbf
Maximum Speed	2520 rpm
Note	This product line was formerly known as " Revolve "